



Waterproof & Dent Resistant Flooring

AQUA DuraCORE / AQUA Technical Specifications by Style

DuraCORE / DFC Luxury Plank	Creation	Duration	Sensation Victory II	Perfection	Lozeta	Classic
Board Size	7" x 48"	7" x 48"	7" x 48"	9" x 60"	18" x 36"	6" x 48"
Overall Thickness	3.5 mm	5.5 mm	6 mm	6 mm	4.5 mm	7.2 mm
Core	DuraCORE	DuraCORE	DuraCORE	DuraCORE	DuraCORE	DFC
Wear Layer	12mil/.30mm	12mil/.30mm	20mil/.50mm	20mil/.50mm	20mil/.50mm	20mil/.50mm
UV Coating	2 Layers	2 Layers	2 Layers	2 Layers	2 Layers	2 Layers
Lifetime Limited Waterproof Warranty	Yes	Yes	Yes	Yes	Yes	Yes
Residential Warranty	20 Years	25 Years	Lifetime	Lifetime	Lifetime	Lifetime
Commercial Warranty	N/A	5 Year Lt. Commercial	15 Year Commercial Warranty	15 Year Commercial Warranty	15 Year Commercial Warranty	15 Year Commercial Warranty
Traffic Wear Rating	Moderate	Moderate	Heavy	Heavy	Heavy	Heavy
Density of Smoke ASTM E 662	Pass	Pass	Pass	Pass	Pass	Pass
Coefficient Wet ASTM C1028-08	0.71	0.71	0.71	0.71	0.71	0.71
Coefficient Dry ASTM C1028-07	0.73	0.73	0.73	0.73	0.73	0.73
IIC ASTM E 90 Drop Ceiling	72	72	72	72	72	72
STC ASTM E 90 Drop Ceiling	73	73	73	73	73	73
IIC ASTM E 90 Floating Slab	57	57	57	57	57	62
STC ASTM E 90 Floating Slab	54	54	54	54	54	59
Radiant Heat Rated	Yes	Yes	Yes	Yes	Yes	Yes
Gloss Levels	7%-10%	7%-10%	7%-10%	7%-10%	7%-10%	7%-10%
Installation	Unilin Click	Unilin Click	I4F Click	I4F Click	I4F Click	I4F Click
Formaldehyde Free ASTM D6007-02	Yes	Yes	Yes	Yes	Yes	Yes
Phthalate Free ASTM F 963-II	Yes	Yes	Yes	Yes	Yes	Yes
FloorScore Conforms to CDPH/EHLB	Yes	Yes	Yes	Yes	Yes	Yes
Flammable Ignition Properties Temp.	454° C	454° C	454° C	454° C	454° C	N/A
Hazard Classification Health-Flammability Reactivity	None	None	None	None	None	N/A

