



UNIFLOOR AQUA Technical Specifications by style

DFC Luxury Clic Plank Floating Floor	UNIFLOOR AQUA CLASSIC	UNIFLOOR AQUA VICTORY 7.5"	UNIFLOOR AQUA VICTORY 6"	UNIFLOOR AQUA VISION	UNIFLOOR AQUA VENTURE
Board Size	5.6" x 48"	7.5" x 48"	5.8" x 48"	5.6" x 48"	5.8" x 48"
Overall Thickness	7.2mm	7.5mm	7.5mm	5mm	6mm
Core	DFC	DFC	DFC	DFC	DFC
Constructions	5.0mm DFC core 2.2mm PVC Top	4.0mm DFC core 1.5mm PVC Top 2.2mm EVA Bottom	4.0mm DFC core 1.5mm PVC Top 2.2mm EVA Bottom	4.0mm DFC core 1.0mm PVC Top	3.0mm DFC core 1.0mm PVC Top 2.2mm EVA Bottom
Wear Layer	.20ml/.50mm	.20ml/.50mm	.20ml/.50mm	.12ml/.30mm	.12ml/.30mm
UV Coating	2	2	2	2	2
Lifetime Limited Waterproof Warranty	Yes	Yes	Yes	Yes	Yes
Lifetime limited Residential Warranty	Yes	Yes	Yes	25 Year	20 Year
15 Year Heavy Commercial	Yes	Yes	Yes	5 Year	No
Commercial Rating	Heavy	Heavy	Heavy	Lt. Comm	Residential
Density of Smoke ASTM E 662	Pass	Pass	Pass	Pass	Pass
Installation	Clic/Float	Clic/Float	Clic/Float	Clic/Float	Clic/Float
Gloss Levels	8%-10%	8%-10%	8%-10%	8%-10%	8%-10%
Coefficient Dry ASTM C1028-07	0.73	0.73	0.73	0.73	0.73
Coefficient Wet ASTM C1028-08	0.71	0.71	0.71	0.71	0.71
IIC Report ASTM E 90	65db	71db	71db	63db	63db
STC ASTM E 90	65db W/Silent73db	73db	73db	63db W/Silent73db	68db
Formaldehyde Free ASTM D6007-02	Yes	Yes	Yes	Yes	Yes
Phthalates Free ASTM F 963-11	Yes	Yes	Yes	Yes	Yes
Materials ASTM F 963-11	Pass	Pass	Pass	Pass	Pass
Density	EN ISO 23996:2012	EN ISO 23996:2013	EN ISO 23996:2014	EN ISO 23996:2015	EN ISO 23996:2016
Radiant Heat	Yes	Yes	Yes	Yes	Yes
FloorScore Conforms to CDPH/EHLB	Yes	Yes	Yes	Yes	No
Silent Shield Underlayment 3mm - Density 3.40 lbs/sqft- STC 73db - IIC 72db - Water Absortion .003 lbs/cuft					